

Use an API Key to Make Calls

Last Modified on 04/12/2023 12:48 pm EDT

To use an API key in the Swagger interface:

1. Log in as an admin and select the appropriate org, if required.
2. Navigate to **Admin > Swagger Docs**.
3. Click the resource from the list to open the Swagger interface in a new tab.
4. Expand a supported endpoint.
5. Enter the API key in the **x-api-key** field to authenticate the call.
6. **Optional:** If impersonation is enabled, enter the ID of the user who will be impersonated. Impersonation can only be enabled by a member of Resolver Support. See [Impersonation with an API Key](#) for more details.

The screenshot shows the Swagger UI for the **POST /data/file/file** endpoint. The interface includes a top navigation bar with 'Tools', 'Swagger Docs', 'Data Import', 'Logo Upload', and 'Data Management Audit Trail'. The endpoint description is 'Post a file to the files service and add reference to the files table'. Below the description, there are three parameters: 'x-api-key' (string, header), 'impersonate-user-id' (number, header), and 'file' (file, required, formData). The 'x-api-key' and 'impersonate-user-id' fields are highlighted with a red box. The 'file' field has a 'Choose File' button and 'No file chosen' text. At the bottom, there is a large blue 'Execute' button.

*The POST /data/file/file endpoint in the **file** service*

7. Complete the remainder of the fields as required.

Example

```
curl -X POST --header 'Content-Type: multipart/form-data' --header 'Accept: application/json' --header 'x-api-key: YOUR_
```

